

# Stainless Steel MultiCartridge Filters

## MICROMATCH 200

Series



### FEATURES OF THE MICROMATCH 200


- + Commercial and Industrial Use
- + Drain and air vent NPT connections
- + 304 stainless steel housing, also available in 316 or 316L stainless steel
- + Accept complete range of filter media
- + Accept 9 3/4" cartridges
- + Use to filter: silt, taste, odor or sediment
- + Flanged inlet and outlet connections
- + Maximum operating pressure: 150 psi
- + Operating temperature: 40°-176°F (4°-80°C)

Model No.	Rated Capacity (GPM)	Dimensions (Inch)		Length of Cartridges (Inch)	No. of Cartridges PCS	Pipe Size (Inch)		
		Width	Height			Inlet/Outlet	Drain	Vent
MM2-3D1L	24	6-3/4	23-1/2	10	3	1	1/4" FNPT	1/4" FNPT
MM2-3D2L	48	6-3/4	33-1/3	20	3	1	1/4" FNPT	1/4" FNPT
MM2-3D3L	72	6-3/4	43-1/4	30	3	1.5	1/4" FNPT	1/4" FNPT
MM2-3D4L	96	6-3/4	53	40	3	1.5	1/4" FNPT	1/4" FNPT
MM2-5D1L	40	8	25-1/2	10	5	1	1/4" FNPT	1/4" FNPT
MM2-5D2L	80	8	35-1/3	20	5	1.5	1/4" FNPT	1/4" FNPT
MM2-5D3L	120	8	45-1/4	30	5	2	1/4" FNPT	1/4" FNPT
MM2-5D4L	160	8	55	40	5	2	1/4" FNPT	1/4" FNPT
MM2-7D1L	56	10	27-1/2	10	7	1.5	1/2" FNPT	1/4" FNPT
MM2-7D2L	112	10	37-1/3	20	7	2	1/2" FNPT	1/4" FNPT
MM2-7D3L	168	10	47-1/4	30	7	2	1/2" FNPT	1/4" FNPT
MM2-7D4L	224	10	57	40	7	2.5	1/2" FNPT	1/4" FNPT

\* Specifications are subject to change without notice

Metric Units	Flowrate (m <sup>3</sup> /hr) = GPM / 4.4	Media (m <sup>3</sup> ) = ft <sup>3</sup> / 35.3	Weight (Kg) = lbs / 2.2	Dimensions (mm) = inch x 25.4
--------------	---	--	-------------------------	-------------------------------

\* Flow shown are based on a maximum flow of 8GPM per sediment cartridge or are limited by the connection size.



**EnviroMatch, Inc.**  
Water and Wastewater Treatment Systems

41601 Cherry Street #B  
Murrieta, CA 92562, USA  
www.enviromatch.com

Tel: +1-949-340-2715  
Fax: +1-949-340-2060  
sales@enviromatch.com

**Exclusive Agent:**