

Stainless Steel MultiBag Filters

MICROMATCH 300

Series



FEATURES OF THE MICROMATCH 300


- + Commercial and Industrial Use
- + Drain and air vent NPT connections
- + 304 stainless steel housing, also available in 316 stainless steel
- + Use to filter: silt, or sediment
- + NPT inlet and outlet connections
- + Maximum operating pressure: 100 psi
- + Operating temperature: 40°-176°F (4°-80°C)
- + Adjustable height

Model	Rated Capacity	Width (Inch)	Bag size (Inch.) (Dia. X Len.)	Pipe Size (Inch)		
	(GPM)			Inlet& Outlet	Drain	Vent
MM3-1	66	12	7" x 16"	2"	1/2"	1/4"
MM3-2	132	12	7" x 32"	2"	1/2"	1/4"

* Specifications are subject to change without notice

Metric Units	Flowrate (m ³ /hr) = GPM / 4.4	Pressure (bar) = PSI / 14.5	Weight (Kg) = lbs / 2.2	Dimensions (mm) = inch x 25.4
---------------------	---	-----------------------------	-------------------------	-------------------------------

* Flow shown are based on a maximum flow of 66GPM per sediment 16" bag or are limited by the connection size.



EnviroMatch, Inc.
Water and Wastewater Treatment Systems

41601 Cherry Street #B
Murrieta, CA 92562, USA
www.enviromatch.com

Tel: +1-949-340-2715
Fax: +1-949-340-2060
sales@enviromatch.com

Exclusive Agent: