

Stainless Steel MultiCartridge Filters

MICROMATCH 400

Series



FEATURES OF THE MICROMATCH 400


- + Commercial and Industrial Use
- + Drain and air vent NPT connections
- + 304 stainless steel housing, also available in 316 or 316L stainless steel
- + Accept complete range of filter media
- + Accept 9 3/4" cartridges
- + Use to filter: silt, taste, odor or sediment
- + Flanged inlet and outlet connections
- + Maximum operating pressure: 150 psi
- + Operating temperature: 40°-176°F (4°-80°C)

| Model No. | Rated Capacity | Dimensions (Inch) | | Length of Cartridges | No. of Cartridges | Pipe Size (Inch) | | |
|-----------|----------------|-------------------|--------|----------------------|-------------------|------------------|-----------|-----------|
| | (GPM) | Width | Height | (Inch) | PCS | Inlet/Outlet | Drain | Vent |
| MM4-5D1L | 40 | 13-3/8 | 29-1/2 | 10 | 5 | 2 | 1/4" FNPT | 1/4" FNPT |
| MM4-5D2L | 80 | 13-3/8 | 39-1/3 | 20 | 5 | 2 | 1/4" FNPT | 1/4" FNPT |
| MM4-5D3L | 120 | 13-3/8 | 49-1/4 | 30 | 5 | 2 | 1/4" FNPT | 1/4" FNPT |
| MM4-5D4L | 160 | 13-3/8 | 59 | 40 | 5 | 2 | 1/2" FNPT | 1/4" FNPT |
| MM4-7D1L | 56 | 15-3/8 | 31-1/2 | 10 | 7 | 2 | 1/2" FNPT | 1/4" FNPT |
| MM4-7D2L | 112 | 15-3/8 | 41-1/3 | 20 | 7 | 2 | 1/2" FNPT | 1/4" FNPT |
| MM4-7D3L | 168 | 15-3/8 | 51-1/4 | 30 | 7 | 2 | 1/2" FNPT | 1/4" FNPT |
| MM4-7D4L | 224 | 15-3/8 | 61 | 40 | 7 | 2 | 1/2" FNPT | 1/4" FNPT |
| MM4-12D3L | 288 | 17-3/8 | 54-3/8 | 30 | 12 | 3 | 3/4" FNPT | 1/4" FNPT |
| MM4-12D4L | 384 | 17-3/8 | 63-3/4 | 40 | 12 | 3 | 3/4" FNPT | 1/4" FNPT |
| MM4-15D3L | 360 | 20-7/8 | 56 | 30 | 15 | 3 | 3/4" FNPT | 1/4" FNPT |
| MM4-15D4L | 480 | 20-7/8 | 65-3/8 | 40 | 15 | 3 | 3/4" FNPT | 1/4" FNPT |
| MM4-19D3L | 456 | 22 | 57-1/2 | 30 | 19 | 4 | 3/4" FNPT | 1/4" FNPT |
| MM4-19D4L | 608 | 22 | 67 | 40 | 19 | 4 | 3/4" FNPT | 1/4" FNPT |
| MM4-27D3L | 648 | 24-3/4 | 60-1/4 | 30 | 27 | 4 | 3/4" FNPT | 1/4" FNPT |
| MM4-27D4L | 864 | 24-3/4 | 69-3/4 | 40 | 27 | 4 | 3/4" FNPT | 1/4" FNPT |

* Specifications are subject to change without notice

| | | | | |
|--------------|---|--|-------------------------|-------------------------------|
| Metric Units | Flowrate (m ³ /hr) = GPM / 4.4 | Media (m ³) = ft ³ / 35.3 | Weight (Kg) = lbs / 2.2 | Dimensions (mm) = inch x 25.4 |
|--------------|---|--|-------------------------|-------------------------------|

* Flow shown are based on a maximum flow of 8GPM per sediment cartridge or are limited by the connection size.



EnviroMatch, Inc.
Water and Wastewater Treatment Systems

41601 Cherry Street #B
Murrieta, CA 92562, USA
www.enviromatch.com

Tel: +1-949-340-2715
Fax: +1-949-340-2060
sales@enviromatch.com

Exclusive Agent: