

Stainless Steel MultiBag Filters

MICROMATCH 700

Series



FEATURES OF THE MICROMATCH 700

- + Commercial and Industrial Use
- + Drain and air vent NPT connections
- + 304 stainless steel housing, also available in 316 stainless steel
- + Accept filter bags 7"(Dia.)x 32"(L)
- + Use to filter: silt and sediment
- + Flanged inlet and outlet connections
- + Maximum operating pressure: 150 psi (10 bar)
- + Operating temperature: 40°-176°F (4°-80°C)

Model	Rated Capacity (GPM)	Dimensions		No. of Bags	Pipe Size (Inch)		
		Width	Height		Inlet& Outlet	Drain	Vent
MM7-2	264	23-1/4	56-1/2	2	3"	1/2	1/4
MM7-3	462	25-1/4	60-5/8	3	3"	1/2	1/2
MM7-4	528	27-1/8	61-3/8	4	4"	1/2	1/2
MM7-4	528	30	64-1/4	4	4"	1/2	1/2
MM7-5	660	32-5/8	68-1/2	5	5"	3/4	1/2
MM7-6	792	33-7/8	70	6	5"	3/5	1/2
MM7-8	1056	36-5/8	75-5/8	8	6"	3/6	3/4
MM7-9	1188	38-5/8	76-3/4	9	6"	3/7	3/4
MM7-10	1320	43-1/4	80-3/4	10	8"	3/8	3/4
MM7-12	1584	47-1/4	82-5/8	12	8"	1	3/4
MM7-16	2112	55-1/8	84-5/8	16	10"	1	3/4
MM7-18	2376	59	92-1/2	18	10"	1-1/4	3/4

* Specifications are subject to change without notice

Metric Units	Flowrate (m ³ /hr) = GPM / 4.4	Pressure (bar) = PSI / 14.5	Weight (Kg) = lbs / 2.2	Dimensions (mm) = inch x 25.4
--------------	---	-----------------------------	-------------------------	-------------------------------

* Flow shown are based on a maximum flow of 132GPM per sediment 32" bag or are limited by the connection



EnviroMatch, Inc.
Water and Wastewater Treatment Systems

41601 Cherry Street #B
Murrieta, CA 92562, USA
www.enviromatch.com

Tel: +1-949-340-2715
Fax: +1-949-340-2060
sales@enviromatch.com

Exclusive Agent: