

# Brackish Water Reverse Osmosis Systems

Capacity: 1,500 to 12,000 GPD

## PUREMATCH 300

Series

### EXCITING FEATURES OF THE PUREMATCH 300 UNITS

- + **High Rejection Levels**  
Rejection Levels as high as 99.4%, producing pure permeate water
- + **High Recovery Levels**  
60% of feed water is recovered as pure RO permeate, reducing waste
- + **Highly Customizable**  
With options to add features pretreatment & posttreatment to meet your unique requirement
- + **Compact Design**  
Vertical single housing arrangement saves space
- + **Quiet Operation**  
Ideal for installations that need to maintain low noise levels
- + **Unbeatable Quality**  
Pre-test and rigorous quality assurance checks prior to shipping assures hassle-free operation
- + **Competitive Pricing**  
An industry leading product, at affordable pricing



### STANDARD FEATURES

- + TFC Spiral Wound Membrane
- + FRP Membrane Housing
- + Stainless Steel Multi Stage Pump
- + 5 Micron Sediment Pre-Filter
- + Powder Coated Steel Frame
- + Digital Conductivity Monitor
- + Stainless Steel Low Pressure Switch
- + Stainless Steel Pre/Post Pressure Gauge
- + Product & Concentrate Flow Meters
- + Stainless Steel Throttling Valves
- + Stainless Steel Inlet Solenoid Valve
- + High Pressure Nylon Tubing
- + Liquid-Tight Wire Shrouding
- + Micro processor based control panel
- + NEMA 12 Enclosure
- + Pretreatment Lockout
- + 208/230V/1 Ph/60Hz Power Supply
- + Programmable set points and time delays
- + Status & Alarm Lights

### AVAILABLE OPTIONS

- + Recycle Flow Meter
- + Stainless Steel Membrane Housing
- + 316 Stainless Steel Kit (Incl. Pump, Valves, Fittings, Pressure Gauge & Switch)
- + Stainless Steel Frame
- + pH & ORP Digital Display
- + Tank Full Level Switch
- + 220V/1 Ph/50Hz Power Supply
- + Stainless Steel High Pressure Switch
- + Automatic Flushing
- + PLC Controller
- + Media Filter Pretreatment
- + Carbon Filter Pretreatment
- + Softener Pretreatment
- + Mixed Bed DI Polisher
- + Export Wood Crating
- + Custom Designed Unit
- + Disassembled Unit Kit

# Brackish Water Reverse Osmosis Systems

Capacity: 1,500 to 12,000 GPD

## PUREMATCH 300

**Series**



### OPERATING SPECIFICATIONS


- + Feed Water Temperature: 100°F max.
- + Feed Water Pressure: 30-75 psi
- + Operating Pressure: 150 - 250 psi.
- + Feed Water TDS: 1,000 ppm
- + pH Range: 5-8
- + Hardness over 1 gpg should be softened
- + Hydrogen Sulfide must be removed
- + Silica Tolerance: 25 ppm max. @ 60% recovery
- + Iron Tolerance: 0.05 ppm max.
- + Turbidity should be <3 NTU
- + Unit can handle higher TDS by lowering recovery

Model	Capacity		4" Membranes	Motor HP		Dimensions L" x W" x H"	Approx. Wt. Lbs
	GPD	M3/D		60Hz	50Hz		
PM3-1500	1500	5.7	1	2	2	21" x 25" x 58"	125
PM3-3000	3000	11.4	2	2	2	21" x 25" x 58"	155
PM3-4500	4500	17	3	2	2	21" x 25" x 58"	175
PM3-6000	6000	22.7	4	2	2	21" x 31" x 58"	195
PM3-7500	7500	28.4	5	3	3	21" x 31" x 58"	215
PM3-9000	9000	34.1	6	3	3	21" x 31" x 58"	235
PM3-10500	10500	39.7	7	3	3	28" x 31" x 58"	255
PM3-12000	12000	45.4	8	3	3	28" x 31" x 58"	275

\* Specifications are subject to change without notice

<b>Metric Units</b>	Pressure (bar) = PSI / 14.5	Power (kW) = HP x 0.746	Weight (Kg) = lbs / 2.2	Dimensions (mm) = inch x 25.4
---------------------	-----------------------------	-------------------------	-------------------------	-------------------------------

\* Purematch 300 systems can be customized for higher feed water TDS of up to 5000 ppm and higher recoveries



**EnviroMatch, Inc.**  
Water and Wastewater Treatment Systems

41571 Corning Place #106  
Murrieta, CA 92562, USA  
www.enviromatch.com

Tel: +1-949-340-2715  
Fax: +1-949-340-2060  
sales@enviromatch.com

**Exclusive Agent:**